

Simplex LWL patch cable LC-LC OS2 2,0mm yellow 9/125µm

Simplex LWL patch cable LC-LC OS2 2,0mm yellow 9/125µm,

the patch cable (also called jumper) has a strain relief reinforced with aramid yarn. It has a halogen-free and flame-retardant sheath in accordance with IEC-60754-2, IEC-60332-1 and IEC-61034. The two LC connectors meet the minimum quality class Grade B/2 in accordance with IEC-61753-1 and are 100% tested with individual measurement protocol.

Fiber type: Singlemode 9/125

Category: OS2

Number of fibres: 1

Anti-buckling grommet: plugged on

Connector type Connection 1: LC

Connector connection 1 Colour: blue

Connector type Connection 2: LC

Connector connection 2 Colour: blue

Cable type: I-V(ZN) H

Cable structure: Simplex

Cable Ø: 2,0 mm

Coat colour: yellow

Jacket material: LSZH

Flame retardant: according to EN 50265-2-1

Working temperature: -20°C - 70°C

Storage temperature: -20°C - 85°C

Quality class singlemode: B/2 according to IEC 61753-1

Cabling standard: EN-50173-1

Cable compliant to standard: IEC 60793-2

Make: EFB-Elektronik GmbH

Item no.: O0948.x

---

Simplex LWL patch cable LC-LC OS2 2,0mm yellow 9/125µm

Simplex LWL patch cable LC-LC OS2 2,0mm yellow 9/125µm,  
as described above, however:

Length: X,Xm

Make: EFB-Elektronik GmbH

Item no.: O0948.XX

---

Structure Art. no:

O0948.XX

.XX = length = "10" = 10,0m

Available in lengths:

0,5m / 1,0m / 10,0m / 15,0m / 2,0m / 25,0m / 3,0m / 5,0m / 6,0m / 7,5m