

FTTH Fiber Pigtail SC 9/125 $\mu$  G657A2, yellow, 2m

FTTH Fiber Pigtail SC 9/125 $\mu$  G657A2, yellow, 2m,

the SC fiber pigtail has a primary coating (900 $\mu$ ) in the color of the respective category, here yellow. The color of the primary and secondary coating is identical. A numeric connector coding 1 ... 12 simplifies the assignment of ports. The pigtails can be ordered individually. Since 12 pigtails are ordered in standard lot sizes, 12 pigtails are contained in one polybag. The separately packed plugs allow quick and convenient removal of each individual pigtail. Each packaging unit contains an individual measuring protocol.

Type: Wire pigtail

Core type: Compact core

Anti-buckling grommet: plugged on

Maximum tractive force: 3 N

Minimum bending radius Static: 10xOD

Minimum bending radius Dynamic: 20xOD

Outer diameter: 0.9 mm

Jacket material: LSZH

length: 2,0 m

Operating temperature: -20°C - 70°C

Plug conforming to standard: IEC 61754-20

Cable compliant to standard: IEC 60793-2

Fiber type: Singlemode

Category: G657A2

Colour: yellow

APC version: No

Plug colour: blue

Connector type: SC

Insertion loss 1310nm: < 0.3 dB

Quality class singlemode: B/2 according to IEC 61753-1

Make: EFB-Elektronik GmbH

Part No.: FTTH-PIGTAIL-SC1

