

Duplex Jumper LC/APC-SC/APC 9/125 $\mu$ , OS2, LSZH, yellow, 2.0mm

Duplex Jumper LC/APC-SC/APC 9/125 $\mu$ , OS2, LSZH, yellow, 2.0mm,

the patch cable (also called jumper) has a strain relief reinforced with aramid yarn. It has a halogen-free and flame-retardant sheath in accordance with IEC-60754-2, IEC-60332-1 and IEC-61034. The two plugs meet quality class Grade B/2 in accordance with IEC-61753-1 and are 100% tested with individual measurement reports.

Fiber type: Singlemode 9/125

Category: OS2

APC version: 8°.

Number of fibres: 2

Anti-buckling grommet: plugged on

Connector type Connection 1: LC duplex

Connector connection 1 Colour: green

Connector type Connection 2: SC-Duplex

Connector connection 2 Colour: green

Maximum tractive force: 160 N

Minimum bending radius (static): 10xOD

Minimum bending radius (dynamic): 20xOD

Cable type: I-V(ZN) H

Cable structure: duplex

Cable  $\varnothing$ : 2,0 mm

Coat colour: yellow

Jacket material: LSZH

Flame retardant: according to EN 50265-2-1

Halogen-free: according to IEC 60754-1

Low smoke: according to IEC 61034-1

Working temperature: -20°C - 70°C

Storage temperature: -20°C - 85°C

Insertion attenuation 1310nm: 0.3 dB

Quality class singlemode: B/2 according to IEC 61753-1

Cabling standard: ISO/IEC 11801; EN-50173-1

Cable compliant to standard: IEC 60793-2

Make: EFB-Elektronik GmbH

Item no.: O0387.x

---

Duplex Jumper LC/APC-SC/APC 9/125 $\mu$ , OS2, LSZH, yellow, 2.0mm

Duplex Jumper LC/APC-SC/APC 9/125 $\mu$ , OS2, LSZH, yellow, 2.0mm,  
as described above, however:

Length: X,Xm

Make: EFB-Elektronik GmbH

Item no.: O0387.XX

---

Structure Art. no:

O0387.XX

.XX = length = "10" = 10,0m

Available in lengths:

1,0m / 2,0m / 3,0m / 5,0m / 7,5m / 10,0m / 15,0m / 20,0m