

Simplex LWL patch cable SC-SC OS2 3,0mm yellow 9/125µm

Simplex LWL patch cable SC-SC OS2 3,0mm yellow 9/125µm,

the patch cable (also called jumper) has a strain relief reinforced with aramid yarn. It has a halogen-free and flame-retardant sheath in accordance with IEC-60754-2, IEC-60332-1 and IEC-61034. The two SC connectors meet the minimum quality class Grade B/2 in accordance with IEC-61753-1 and are 100% tested with individual measurement protocol.

Fiber type: Singlemode 9/125

Category: OS2

Number of fibres: 1

Anti-buckling grommet: plugged on

Connector type Connection 1: SC

Connector connection 1 Colour: blue

Connector type Connection 2: SC

Connector connection 2 Colour: blue

Cable type: I-V(ZN) H

Cable structure: Simplex

Cable Ø: 3,0 mm

Coat colour: yellow

Jacket material: LSZH

Flame retardant: according to EN 50265-2-1

Working temperature: -20°C - 70°C

Storage temperature: -20°C - 85°C

Quality class singlemode: B/2 according to IEC 61753-1

Cabling standard: ISO/IEC 11801; EN-50173-1

Cable compliant to standard: IEC 60793-2

Make: EFB-Elektronik GmbH

Item no.: O1323.x

Simplex LWL patch cable SC-SC OS2 3,0mm yellow 9/125µm

Simplex LWL patch cable SC-SC OS2 3,0mm yellow 9/125µm,
as described above, however:

Length: X,Xm

Make: EFB-Elektronik GmbH

Item no.: O1323.XX

Structure Art. no:

O1323.XX

.XX = length = "10" = 10,0m

Available in lengths:

0.5m / 1.0m / 10.0m / 15.0m / 2.0m / 20.0m / 3.0m / 5.0m / 7.5m